PETRI DISHES FILLER

An industrial tool for all laboratories







Dispensing accuracy +/- 1ml



High production throughput



Compatible with most Petri dishes (55 and 90mm)



Built-in Peltier cooling effectReduces condensation and solidification time



Plate Pouring System Option

Aerobiocontamination prevention

During distribution with UV lamp and plexiglas cover

In-line blood addition Option

... Multicolored visual alarm



Integrated bubble level

To warranty a flat poured media













Delivered with the DISTRIWEL: User Manual, Power supply cable, Tubing sets x2 (DISW2005), Certificate of conformance, FHC screws, Stainless steel washers M4 x6, Stainless steel washers M5 x6, Linx printer fiting kit (only in DISW1003)

etri dishes per hour	Up to 880
Distribution modes	Automatic with carrousel and manual
Capacity	440 Petri dishes
Fast cooling	Built-in Peltier effect
Contamination prevention	Built-in UV lamp
Distribution speed	From 30 to 300 RPM
Distribution accuracy	± 1ml
Distribution volume	1-99ml
Stack plates function	√
Peristaltic pump	Integrated pump (double pump in option)
Programs	40
Touchscreen	Tactile, LCD 7"
Fraceability	Ink jet printer on the Petri dish sides (also possible from the bottom of the dish, on demand).
ootswitch (for manual distribution)	√ (option)
Dimensions (L x I x H)	689 x 808 x 940 mm
Veight	71 kg
Power supply	115 or 230 V - ± 10% - 50/60 Hz - 3A max - 150 W
Country of origin	France - European Union
Warranty	1 year
CONFIGURATIONS	
DISW1001P	Distriwel with blood addition kit
DISW1001X	Distriwel with LINX printer kit
DISW1001XP	Distriwel with blood addition + LINX printer kit
DISW1001S	Distriwel with plate pouring system

DISTRIWEL®

Blood addition kit (DISW1001P):



Inkjet Printer (LINX8900):



